

# PH 66 O

Open sun shading screen

# Technical data sheet

### **Product description**

Type of product	Woven Fabric	Application	Indoor
Colour	Aluminum	Material	Alu/Acryl

## **Properties**

Physical Properties	Standard	Performance	Tolerance	
Weight	EN ISO 9864	73 g/m²	±7,3 g/m²	
Length		As required -		
Roll Width		325-430-480 cm	±2 cm	
		127,9-169,3-189,0 in	±0,8 in	
Mechanical Properties	Standard	Performance		
Energy saving	Phormium test method	25 %		
Direct Light transmission	Phormium test method	35 %		
Shading	Phormium test method	65 %		
Shrinkage	2h at 70°C	≤1 %		
Durability	Standard	Performance		
	DIN 4102	-		
Flame retardant	NTA 8825			
name reididdin	ASTM E 84			
	NFPA 701 - 2015 Test Method 2			

#### Warranty

Under all types of greenhouse covering 8 years, see Phormiums limited warranty for all terms, conditions, and exclusions in writing.

#### Remarks

The Quality Management System of IFG Cresco has been approved to the ISO 9001 / ISO 14001 Quality Management System Standard. Certificates are available on request. The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.





019 - EMS

IFG Cresco, a division of IFG Exelto N.V. Weverslaan 15, 9160 Lokeren, Belgium info@phormium.com / www.phormium.com -

Version n°