

## Ridder Sun Shading Screens Open Aluminium Black External (RSS 15 O AB E)

| Product information                  |   |                               |  |  |  |  |  |  |  |
|--------------------------------------|---|-------------------------------|--|--|--|--|--|--|--|
| Application                          | Outside   |                               |  |  |  |  |  |  |  |
| Main Function                        | Daytime sun shading with ventilation  |                               |  |  |  |  |  |  |  |
| System                               | Sliding and Hanging   |                               |  |  |  |  |  |  |  |
| Composition                          | 73% Polyolefin, 27% Aluminium   |                               |  |  |  |  |  |  |  |
| Pattern                              | 1 aluminium black, 1 open   |                               |  |  |  |  |  |  |  |
| Yarn                                 | Black yarns   |                               |  |  |  |  |  |  |  |
| Flame retardant                      | No,   |                               |  |  |  |  |  |  |  |
| Warranty                             | Three years for outdoor applications. See the Ridder Climate Screens limited warran |                               |  |  |  |  |  |  |  |
| Mechanical properties                | Value   | Testing method                |  |  |  |  |  |  |  |
| Screen weight                        | 144 gr/m2   |                               |  |  |  |  |  |  |  |
| Width of strips                      | 4 mm  |                               |  |  |  |  |  |  |  |
| Physical properties                  | Value   | Testing method                |  |  |  |  |  |  |  |
| Shading level in direct light PAR*   | 58 %  | Ridder Climate Screens method |  |  |  |  |  |  |  |
| Shading level in diffused light PAR* | 62 %  | Ridder Climate Screens method |  |  |  |  |  |  |  |
| Energy saving*                       | 23 %  | Ridder Climate Screens method |  |  |  |  |  |  |  |

\*PAR = 400 - 700 nm, accuracy +/- 1%



The Ridder Sun-Shading Screen prevents damage to crops from excessive sunlight. This climate screen also saves energy and is able to prevent condensation from forming due to sudden drops in temperature.

Whether you are growing in a tropical climate or a temperate climate, with Ridder Sun Shading Screens your plants will thrive in a shady environment.

| Screentype   | Material |       | Composition    |           | Shading level* |         | NEN 2675:2018 |         |                  | Energy  | ĺ         | Weight |  |
|--|----------|-------|----------------|-----------|----------------|---------|---------------|---------|------------------|---------|-----------|--------|--|
|  | Strips   | Yarn  | Polyolefin     | Polyester | Direct         | Diffuse | Direct        | Diffuse | Horti<br>Scatter | saving* | NTA Class | gr/m2  |  |
| Ridder Sun Shading Screens Open                          |          |       |                |           |                |         |               |         |                  |         |           |        |  |
| RSS 15 FR O  | ALU      | PET   | 39%            | 61%       | 55%            | 60%     | -             | -       | -                | 23%     | 1         | 74     |  |
| RSS 16 FR O  | ALU      | PET   | 39%            | 61%       | 66%            | 67%     | 68%           | 71%     | 13%              | 28%     | 1         | 87     |  |
| RSS 17 FR O  | ALU      | PET   | 39%            | 61%       | 76%            | 78%     | 78%           | 79%     | 16%              | 30%     | 1         | 96     |  |
| RSS 15 O   | PET/ALU  | PET   | 54%            | 46%       | 52%            | 55%     | -             | -       | -                | 23%     | -         | 65     |  |
| RSS 16 O   | PET/ALU  | PET   | 46%            | 54%       | 60%            | 63%     | -             | -       | -                | 28%     | -         | 65     |  |
| RSS 17 O   | PET/ALU  | PET   | 55%            | 45%       | 70%            | 73%     | -             | -       | -                | 30%     | -         | 73     |  |
| Ridder Sun Shading Screens Open Aluminium Black External |          |       |                |           |                |         |               |         |                  |         |           |        |  |
| RSS 14 O AB E  | ALU      | PE    | 78%            | 22% alu   | 46%            | 50%     | -             | -       | -                | 20%     | -         | 136    |  |
| RSS 15 O AB E  | ALU      | PE    | 73%            | 27% alu   | 58%            | 62%     | -             | -       | -                | 23%     | -         | 144    |  |
| RSS 16 O AB E  | ALU      | PE    | 68%            | 32% alu   | 68%            | 70%     | -             | -       | -                | 25%     | -         | 156    |  |
| Side Hanging cloth for RES,<br>RLD & RSS cloths          | Material |       | Length of roll |           | Shading level* |         | NEN 2675:2018 |         | Energy           |         |           |        |  |
|  |          |       |                |           | Direct         | Diffuse | Direct        | Diffuse | Horti<br>Scatter | saving* | NTA Class | gr/m2  |  |
| Ridder White FR  | Poly     | ester | ± 150          | ),00m     | 55%            | 55%     | -             | -       | -                | 43%     | 1         | 195    |  |

\*According to Ridder Climate Screens