

Ridder Sun Shading Screens Open (RSS 17 FR O)

Product information

Application Inside

Main Function Daytime sun shading with ventilation

System Sliding and Hanging

Composition 39% Polyolefin, 61% Polyester Pattern 3 aluminum/white, 1 open

Yarn White yarns

Flame retardant Yes, NTA 8825:2018

Warranty Five years under all types of greenhouse covering, see Ridder Climate Screens limited

warranty.

Mechanical properties	Value	Testing method
Screen weight	96 gr/m2	
Width of strips	4 mm	

Physical properties	Value	Testing method
Shading level in direct light PAR*	76 %	Ridder Climate Screens method
	78 %	NEN 2675:2018
Shading level in diffused light PAR*	78 %	Ridder Climate Screens method
	79 %	NEN 2675:2018
HortiScatter	16 %	NEN 2675:2018
Energy saving*	30 %	Ridder Climate Screens method

^{*}PAR = 400 - 700 nm, accuracy +/- 1%





The Ridder Sun-Shading Screen prevents damage to crops from excessive sunlight.

This climate screen also saves energy and is able to prevent condensation from forming due to sudden drops in temperature.

Whether you are growing in a tropical climate or a temperate climate, with Ridder Sun Shading Screens your plants will thrive in a shady environment.

Screentype	Material		Composition		Shading level*		NEN 2675:2018			Energy		Weight
	Strips	Yarn	Polyolefin	Polyester	Direct	Diffuse	Direct	Diffuse	Horti Scatter	saving*	NTA Class	gr/m2
Ridder Sun Shading Screens Open												
RSS 15 FR O	ALU	PET	39%	61%	55%	60%	-	-	-	23%	1	74
RSS 16 FR O	ALU	PET	39%	61%	66%	67%	68%	71%	13%	28%	1	87
RSS 17 FR O	ALU	PET	39%	61%	76%	78%	78%	79%	16%	30%	1	96
RSS 15 O	PET/ALU	PET	54%	46%	52%	55%	-	-	-	23%	-	65
RSS 16 O	PET/ALU	PET	46%	54%	60%	63%	-	-	-	28%	-	65
RSS 17 O	PET/ALU	PET	55%	45%	70%	73%	-	-	-	30%	-	73
Ridder Sun Shading Screens Open Aluminium Black External												
RSS 14 O AB E	ALU	PE	78%	22% alu	46%	50%	-	-	-	20%	-	136
RSS 15 O AB E	ALU	PE	73%	27% alu	58%	62%	-	-	-	23%	-	144
RSS 16 O AB E	ALU	PE	68%	32% alu	68%	70%	-	-	-	25%	-	156
Side Hanging cloth for RES, RLD & RSS cloths					Shading level*		NEN 2675:2018		Energy			
	Mat	Material Length of rol		of roll	Direct	Diffuse	Direct	Diffuse	Horti Scatter	saving* NTA Clas	NTA Class	gr/m2
Ridder White FR	Poly	ester	± 150),00m	55%	55%	-	-	-	43%	1	195

^{*}According to Ridder Climate Screens